

flush
bündig
M8x1 | 1 mm



flush
bündig
M8x1 | 1 mm



flush
bündig
M8x1 | 1 mm




flush
bündig
M8x1 | 1 mm




non-flush
nicht bündig
M8x1 | 2 mm




standard
Standard




standard
Standard




standard
Standard



standard
Standard



standard
Standard



1 mm		1 mm		1 mm		1 mm		2 mm	
10...30 V _{DC}		10...30 V _{DC}		10...30 V _{DC}		10...30 V _{DC}		10...30 V _{DC}	
built-in	integriert	built-in	integriert	built-in	integriert	built-in	integriert	built-in	integriert
<8 mA		<8 mA		<8 mA		<8 mA		<8 mA	
200 mA		200 mA		200 mA		200 mA		200 mA	
built-in	integriert	built-in	integriert	built-in	integriert	built-in	integriert	built-in	integriert
<1.5 V @ 200 mA		<1.5 V @ 200 mA		<1.5 V @ 200 mA		<1.5 V @ 200 mA		<1.5 V @ 200 mA	
2000 Hz		2000 Hz		2000 Hz		2000 Hz		2000 Hz	
Alu 0.45 · Brs 0.50 · SS 0.85		Alu 0.45 · Brs 0.50 · SS 0.85		Alu 0.45 · Brs 0.50 · SS 0.85		Alu 0.45 · Brs 0.50 · SS 0.85		Alu 0.45 · Brs 0.50 · SS 0.85	
–25...+75 °C		–25...+75 °C		–25...+75 °C		–25...+75 °C		–25...+75 °C	
IP67		IP67		IP67		IP67		IP67	
POM		POM		POM		POM		POM	
SS304	V2A	SS304	V2A	SS304	V2A	SS304	V2A	SS304	V2A
built-in	integriert	built-in	integriert	built-in	integriert	built-in	integriert	built-in	integriert
PVC, ultra-flex		conn. M8 Stecker M8		conn. M8 Stecker M8		conn. M12 Stecker M12		PVC, ultra-flex	
IPS8-S1PO45-A2P		IPS8-S1PO45-A8		IPS8-S1PO60-A8		IPS8-S1PO70-A12		IPS8-N2PO30-A2P	
IPS8-S1PC45-A2P		IPS8-S1PC45-A8		IPS8-S1PC60-A8		IPS8-S1PC70-A12		IPS8-N2PC30-A2P	
IPS8-S1NO45-A2P		IPS8-S1NO45-A8		IPS8-S1NO60-A8		IPS8-S1NO70-A12		IPS8-N2NO30-A2P	
IPS8-S1NC45-A2P		IPS8-S1NC45-A8		IPS8-S1NC60-A8		IPS8-S1NC70-A12		IPS8-N2NC30-A2P	