



CSS 14-34-S-D-M-ST

- 1 x connector plug M12, 8-pole
- Actuation from side
- Max. 31 sensors can be wired in series.
- Thermoplastic enclosure
- Electronic contact-free, coded system
- Misaligned actuation possible
- 27 mm x 108.2 mm x 35 mm
- High repeat accuracy of the switching points
- Max. length of the sensor chain 200 m
- 2 short-circuit proof PNP safety outputs
- Integral cross-short, wire-breakage and external voltage monitoring of the safety cables up to the control cabinet

Data

Ordering data

Product type description	CSS 14-34-S-D-M-ST
Article number (order number)	101181063
EAN (European Article Number)	4030661314877
eCl@ss number, version 12.0	27-27-46-01
eCl@ss number, version 11.0	27-27-24-03
eCl@ss number, version 9.0	27-27-24-03
ETIM number, version 7.0	EC001829
ETIM number, version 6.0	EC001829

Approvals - Standards

General data

Standards	EN IEC 60947-5-3
Working principle	inductive
Housing construction form	Block
Installation conditions (mechanical)	not flush
Sensor topology	Sensor for series wiring
Housing material	Glass-fibre, reinforced thermoplastic
Active area	Glass-fibre, reinforced thermoplastic
Reaction time, maximum	30 ms
Duration of risk, maximum	60 ms
Gross weight	140 g

General data - Features

Diagnostic output	Yes
Short circuit detection	Yes
Cross-circuit detection	Yes
Safety functions	Yes
Cascadable	Yes
Integral system diagnostics, status	Yes
Number of LEDs	3
Number of semi- conductor outputs with signaling function	1
Number of fail-safe digital outputs	2
Number of series-wiring of sensors	31

Safety classification

Standards	EN ISO 13849-1 EN IEC 60947-5-3 EN IEC 61508
Performance Level, up to	e
Category	4
PFH value	3.60×10^{-9} /h
Safety Integrity Level (SIL), suitable for applications in	3
Mission time	20 Year(s)

Mechanical data

Actuating panels	lateral
Active area	lateral
Switching distance actuator	Actuator CST 34-V-1: 10 mm (typical switch distance Sn) Betätiger CST 34-V-1: 8 mm (gesicherter Schaltabstand EIN Sao) Betätiger CST 34-V-1: 13 mm (gesicherter Schaltabstand AUS Sar) Actuator CST 34-S-1 / CST 34-S-3: 14 mm (typical switch distance Sn) Actuator CST 34-S-1 / CST 34-S-3: 12 mm (ensured switch distance ON Sao) Actuator CST 34-S-1 / CST 34-S-3:: 17 mm (ensured switch distance OFF Sar) Actuator CST 34-S-2: 14 mm (typical switch distance Sn) Actuator CST 34-S-2: 12 mm (ensured switch distance ON Sao) Betätiger CST 34-S-2: 17 mm (gesicherter Schaltabstand AUS Sar) Betätiger CST 180-1 / CST 180-2: 10 mm (typischer Schaltabstand Sn) Actuator CST 180-1 / CST 180-2: 8 mm (ensured switch distance ON Sao) Actuator CST 180-1 / CST 180-2: 13 mm (ensured switch distance OFF Sar)

Mechanical data - Switching distances

Hysteresis (Switching distance), maximum	1.5 mm
Repeat accuracy R	0.5 mm
Note (Repeat accuracy R)	Axial offset: The long side allows for a maximum height misalignment (x) of sensor and actuator of 36 mm (e.g. mounting tolerance or due to guard door sagging). Increased misalignment, max. 53 mm, possible when the CST 34-S-2 actuator is used. The axial misalignment (y) is max. ± 10 mm (see figure: Operating principle)

Mechanical data - Connection technique

Note (length of the sensor chain)	Cable length and cross-section change the voltage drop depending on the output current
Termination	Connector plug M12, 8-pole

Mechanical data - Dimensions

Length of sensor	35 mm
Width of sensor	27 mm
Height of sensor	108.2 mm

Ambient conditions

Degree of protection	IP65 IP67
Ambient temperature	-25 ... +70 °C
Storage and transport temperature	-25 ... +85 °C
Resistance to vibrations	10 ... 55 Hz, amplitude 1 mm
Resistance to shock	30 g / 11 ms
Protection class	II

Ambient conditions - Insulation values

Rated insulation voltage U_i	32 VDC
Rated impulse withstand voltage U_{imp}	0.8 kV
Overvoltage category	III
Degree of pollution	3

Electrical data

No-load supply current I_0 , typical	100 mA
Operating current	600 mA

Required rated short-circuit current	100 A
Note (Electrical data, Fuse rating)	(Circuit breaker)
Switching frequency, approx.	3 Hz
Utilisation category DC-12	24 VDC / 0.05 A

Electrical data - Safety digital outputs

Rated operating current (safety outputs)	250 mA
Output current, (fail-safe output), maximum	0.25 A
Design of control elements	p-type
Voltage drop U_d , maximum	0.5 V
Leakage current I_r , maximum	0.5 mA
Voltage, Utilisation category DC-12	24 VDC
Current, Utilisation category DC-12	0.25 A
Voltage, Utilisation category DC-13	24 VDC
Current, Utilisation category DC-13	0.25 A

Electrical data - Diagnostic outputs

Design of control elements	p-type
Voltage drop U_d , maximum	5 V
Voltage, Utilisation category DC-12	24 VDC
Current, Utilisation category DC-12	0.05 A

Voltage, Utilisation
category DC-13

24 VDC

Current, Utilisation
category DC-13

0.05 A

Electrical data - Electromagnetic compatibility (EMC)

Interfering radiation

IEC 61000-6-4

EMC rating

IEC 61000-6-2

Pin assignment

PIN 1	1A1 Ue: (1)
PIN 2	X1 Safety input 1
PIN 3	A2 GND
PIN 4	Y1 Safety output 1
PIN 5	OUT Diagnostic output OUT
PIN 6	X2 Safety input 2
PIN 7	Y2 Safety output 2
PIN 8	IN without function

Scope of delivery

Scope of delivery

Actuator must be ordered separately.

Accessory

Recommendation (actuator)	CST 34-S-2 CST 34-S-3 CST 180-1 CST 180-2 CST 34-S-1
Recommended safety switchgear	PROTECT PSC1 SRB-E-301ST SRB-E-201LC

Note

Note (General)

Evaluation requirements: dual-channel safety input, suitable for p-type sensors with NO function. The safety-monitoring module must tolerate internal functional tests of the sensors with cyclic switch-off of the sensor outputs for max. 0.5 ms. Short-circuit recognition by the evaluation is not necessary.

Ordering code

Product type description:
CSS (1)-34-(2)-(3)-(4)-M-(5)

(1)

12 Actuation from top

14 Actuation from side

(2)

without Standard version

F0 Input for enabling pushbutton, suitable for automatic start

F1 Input for reset pushbutton, with edge monitoring

(3)

S lateral active surface

V frontal active surface

(4)

D With diagnostic output

SD Serial diagnostic output

(5)

L with connecting cable

ST with connector

Pictures

Product picture (catalogue individual photo)



ID: kc33f10


| 238.3 kB | .jpg | 352.778 x 235.303 mm - 1000 x 667 px - 72 dpi

| 24.8 kB | .png | 74.083 x 49.389 mm - 210 x 140 px - 72 dpi

| 24.3 kB | .png | 74.083 x 74.083 mm - 210 x 210 px - 72 dpi

| 1.8 MB | .png | 166.557 x 111.094 mm - 2000 x 1334 px - 305 dpi

Dimensional drawing basic component




ID: 1css3g01

| 50.7 kB | .cdr |

| 4.4 kB | .png | 73.731 x 79.022 mm - 209 x 224 px - 72 dpi

| 204.8 kB | .jpg | 352.778 x 377.119 mm - 1000 x 1069 px - 72 dpi

Contact arrangement




ID: km23-k8b

| 5.3 kB | .png | 73.731 x 79.728 mm - 209 x 226 px - 72 dpi

| 139.8 kB | .jpg | 352.778 x 380.647 mm - 1000 x 1079 px - 72 dpi

Operating principle




ID: kc33a02

| 46.4 kB | .cdr |

| 321.9 kB | .jpg | 352.778 x 796.219 mm - 1000 x 2257 px - 72 dpi

| 5.5 kB | .png | 74.083 x 167.217 mm - 210 x 474 px - 72 dpi

Clipart



ID: kc5s3c06

| 16.0 kB | .cdr |

| 932.0 b | .png | 74.083 x 35.983 mm - 210 x 102 px - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 27/02/2026, 14:55