



## BNS 260-02Z-ST-L

- Connector M8 x 1, 4-pole
- Thermoplastic enclosure
- small body
- Concealed mounting possible
- 26 mm x 36 mm x 13 mm
- Long life
- no mechanical wear
- Insensitive to transverse misalignment
- Insensitive to soiling

## Data

### Ordering data

Product type description	BNS 260-02Z-ST-L
Article number (order number)	101184377
EAN (European Article Number)	4030661321752
eCl@ss number, version 12.0	27-27-44-01
eCl@ss number, version 11.0	27-27-24-02
eCl@ss number, version 9.0	27-27-24-02
ETIM number, version 7.0	EC002544
ETIM number, version 6.0	EC002544

### Approvals - Standards

Certificates	cULus
--------------	-------

### General data

Standards	BG-GS-ET-14 EN IEC 60947-5-3
Coding level according to EN ISO 14119	Low
Working principle	Magnetic drive
Installation conditions (mechanical)	quasi-flush
Housing material	Glass-fibre, reinforced thermoplastic
Gross weight	32 g

### General data - Features

Coding	Yes
Number of normally closed (NC)	2
Number of safety contacts	2

### Safety classification

Standards	EN ISO 13849-1
Mission time	20 Year(s)

### Safety classification - Safety outputs

B <sub>10D</sub> Normally-closed contact (NC)	25,000,000 Operations
B <sub>10D</sub> - Value Normally-closed contact/Normally open contact (NC/NO)	25,000,000 Operations

### Mechanical data

Actuating element	Magnet
Door hinge	Left
Direction of motion	Head-on to the active surface

## Mechanical data - Switching distances

Note (Switching distance $S_n$ )	Axial misalignment, a horizontal and vertical misalignment of the safety sensor and the actuator are tolerated. The possible misalignment depends on the distance of the active surfaces of the sensor and the actuator. The sensor remains active within the tolerance range.
Assured switching distance "ON" $S_{ao}$	5 mm
Assured switching distance "OFF" $S_{ar}$	15 mm
Note (switching distance)	All switching distances in accordance EN IEC 60947-5-3

## Mechanical data - Connection technique

Termination	Connector M8
Tightening torque of electrical connection	0.3 Nm

## Mechanical data - Dimensions

Length of sensor	13 mm
Width of sensor	26 mm
Height of sensor	36 mm

## Ambient conditions

Degree of protection	IP67
Ambient temperature	-25 ... +70 °C
Storage and transport temperature	-25 ... +70 °C
Resistance to vibrations	10 ... 55 Hz, amplitude 1 mm
Resistance to shock	30 g / 11 ms

## Ambient conditions - Insulation values

Rated insulation voltage $U_i$	50 VAC 75 VDC
--------------------------------	------------------

Rated impulse withstand  
voltage  $U_{imp}$  0.8 kV

## Electrical data

Required rated short-circuit  
current 100 A

Switching voltage, maximum 30 VDC

Switching current, maximum 0.4 A

Switching capacity, maximum 10 VA

Switching element 2 NC contact

Switching frequency,  
maximum 5 Hz

## Scope of delivery

Scope of delivery Actuator must be ordered separately.

## Accessory

Recommendation (actuator) BPS 260

Recommended safety  
switchgear SRB-E-301ST  
SRB-E-201LC

## Note

Note (General) The number in brackets indicate the PIN number of the connector.

## Wiring example

Note (Wiring diagram) The contacts S11-S12 and S21-S22 must be integrated in the safety circuit.

## Ordering code

Product type description:  
BNS 260-(1)(2)Z(3)-(4)-(5)

(1)		
<b>11</b>		1 NO contact/1 NC contact
<b>02</b>		2 NC contact
(2)		
<b>without</b>		without diagnostic output
<b>/01</b>		1 NC contact
(3)		
<b>without</b>		without LED switching conditions display
<b>G</b>		with LED switching conditions display
(4)		
<b>without</b>		Pre-wired cable
<b>ST</b>		with connector
(5)		
<b>L</b>		Door hinge on left-hand side
<b>R</b>		Door hinge on right-hand side

## Pictures

### Product picture (catalogue individual photo)



ID: kbns2f25


| 665.5 kB | .jpg | 352.778 x 542.219 mm - 1000 x 1537 px - 72 dpi

| 93.8 kB | .png | 73.731 x 113.594 mm - 209 x 322 px - 72 dpi

| 41.1 kB | .png | 74.083 x 74.083 mm - 210 x 210 px - 72 dpi

| 7.5 MB | .png | 169.333 x 260.35 mm - 2000 x 3075 px - 300 dpi

### Dimensional drawing basic component




ID: 1bns2g06

| 25.6 kB | .cdr |

| 3.1 kB | .png | 74.083 x 51.506 mm - 210 x 146 px - 72 dpi

| 65.1 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695 px - 72 dpi

## Diagram




ID: kbns2k25

| 56.8 kB | .jpg | 352.778 x 70.203 mm - 1000 x 199 px - 72 dpi

| 2.6 kB | .png | 74.083 x 14.817 mm - 210 x 42 px - 72 dpi

## Characteristic curve




ID: kbns2d03

| 18.5 kB | .png | 74.083 x 49.036 mm - 210 x 139 px - 72 dpi

| 200.1 kB | .jpg | 352.778 x 233.892 mm - 1000 x 663 px - 72 dpi

## Characteristic curve




ID: kbns2d02

| 19.2 kB | .png | 74.083 x 49.389 mm - 210 x 140 px - 72 dpi

| 200.9 kB | .jpg | 352.778 x 235.303 mm - 1000 x 667 px - 72 dpi

## Contact arrangement




ID: km8--k4b

| 17.0 kB | .cdr |

| 4.3 kB | .png | 74.083 x 73.025 mm - 210 x 207 px - 72 dpi

| 110.6 kB | .jpg | 352.778 x 347.133 mm - 1000 x 984 px - 72 dpi

## Clipart



ID: kbns2c02

| 19.6 kB | .cdr |

| 1.8 kB | .png | 74.083 x 52.211 mm - 210 x 148 px - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 27/02/2026, 14:51